

DH-PFS3005-5ET-L

5-Port Desktop Fast Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7x24H: Stable performance for long-term operation

System Overview

5 × 10/100 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

Technical Specification

Performance

Layer Layer 2

Managed No

Hardware

Standard Power Supply Yes

PoE No

Ethernet Port 5

Ethernet Port Rate 100 Mbps

Power Supply 5V/500mA DC

Operating Temperature -10°C to 55°C (14°F to 131°F)

Operating Humidity 10%–90%

Storage Temperature -20°C to 70°C (-4°F to 158°F)

Storage Humidity 10%–90%

Power Consumption Idling: 0.65W
Full load: 1.3W

Performance

Switching Capacity 1 Gbps

Packet Forwarding Rate 0.744 Mpps

Packet Buffer Memory 448 Kbits

MAC Table Size 1K

Standards Compliance IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3az

Application

The product is applicable to small and medium office and home networks.

General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.04 kg (0.09 lb)
Gross Weight	0.14 kg (0.31 lb)
Dimensions	77 mm × 46 mm × 21 mm (3.03" × 1.81" × 0.83")
Packaging Dimensions	94 mm × 55 mm × 107 mm (3.70" × 2.17" × 4.21")

Dimensions (mm[inch])

