

The BG500 barrier gate equips with a high-performance safe low voltage DC brushless motor, offering stable and reliable operation, and adopts digital coding control to respond efficiently and sensitively.

The all-in-one worm gear reducer transmission mechanism is easy to install and maintain and has a good load capacity, and supports various barrier arm types.

Features



Highly energy-efficient because of the DC brushless motor



The barrier arm will rebound when an obstacle detected



Manual rise and fall in case of absence of power



Easy to maintain, thanks to the modular construction



Simple and compact transmission mechanism



Adjustable opening and closing speed from 1.5s to 6s



Digital control mainboard with diverse configuration possibilities



Reversible boom direction



Barrier arm's length from 3m to 6m



Accurate and safe operation with the digital encoder

|--|

Adjustable angle of rise/fall


[]		0
I	00	00

Various barrier arm

Specifications

Model	BG530L/R	BG545L/R	BG560L/R	BG545L/R-LED	BG545L/R-90	BG545L/R-F		
Operating Speed	1.5s	2.5s	5s	2.5s	3s	Зs		
Boom Length	3m	4.5m	бm	4.5m	4.5m	4.5m		
Boom Type	Straight boom	Telescopic boom		Straight boom with LED	Folding boom	Fence boom		
Motor Type	DC 24V brushless motor							
Output Power	160W							
Output Current	10A							
Operating Voltages	DC 24V							
Power Supply	AC 220V/110V, 50Hz to 60Hz							
MCBF	2million times							
Remote Control Distance	≥30m							
Operating Temperature	-30°C to 75°C							
Protection Level	IP54							
Chassis Dimensions (mm)	350*270*1020mm							
Net Weight (excluding the barrier arm)	43kg							


Directions





L:The chassis on the left, the boom on the right


R: The chassis on the right, the boom on the left



(Support customization, remark the total length in the purchase order)

Default height∶H≤0.89m

Related Products





.....

Copyright@2022 ZKTECO CO., LTD. All rights reserved.

V5.0 07/19/2022